












**Fluoramics, Inc.** Better Engineered thread sealants, lubricants and rust prohibitors

<p>Lox 8 Paste</p>		<p><b><u>Lox 8 Paste</u></b> Product description: LOX-8 Thread Sealant Paste is a superior thread sealant for use in applications requiring oxygen-safe, waterproof ( or dry) conditions. LOX 8 Paste is perfect for lubricating o-rings, gaskets and seals while performing in both extreme high temperatures and pressure.</p>
<p>Lox 8 Grease</p>		<p><b><u>Lox 8 Grease</u></b> Product description: LOX 8 Grease, being thinner, is perfect to be used to lubricate bearings and other surfaces where severe oxidizers are present.</p>
<p>Chem 8</p>		<p><b><u>Chem 8</u></b> Product description: CHEM-8 is a great lubricant where sophisticated chemicals are packaged, or where corrosion or rusting is a problem. It is especially suitable for mechanical instruments such as hinges, where repeated autoclaving is required. Use as a pipe joint sealer for aqueous systems like water systems, and steam lines. It is waterproof, effective to 300°F, and chemically inert. CHEM-8 stays put and lasts indefinitely.</p>
<p>Formula 8</p>		<p><b><u>Formula 8</u></b> Product description: FORMULA-8 is specifically made for use as a thread sealant in non-aqueous conditions. It uses PTFE in a white thixotropic paste to seal threaded joints. The seals are formed over the entire thread length.</p>
<p>HinderRust R2.0</p>		<p><b><u>HinderRust R2.0</u></b> Product description: HinderRust R2.0 is a temporary Surface Protection for metal parts that need protection after fabrication, while sitting in inventory, or during transportation to the end user. Removable by washing to allow for final finishing. HinderRUST is a long lasting, VOC-free, non-solvent rust inhibitor and lubricant.</p>



<p>HinderRust S4.0</p>		<p><b><u>HinderRust S4.0</u></b> Product description:</p> <p>HinderRust S4.0 provides surface protection for metal parts that need protection before and after exposure to the elements. Engineered to stop rust before it starts, and to stop rust that has started. Strong surface adhesion, very hard to remove by exposure to normal weather elements.</p>
<p>Industrial Tufoil</p>		<p><b><u>Industrial Tufoil</u></b> Product description:</p> <p>Industrial Tufoil is a precisely formulated blend of synthetic and mineral oils with electrostatically charged submicron particles of PTFE and soluble molybdenum compound suspended in and dispersed throughout the carrier. Used in machinery, it reduces wear, noise, vibration and friction while improving production and cutting downtime. It reduces heat and operating oil temperatures, lowers starting torque, extends oil-drain intervals, eliminates sheet metal cracking, cuts waste, and speeds production.</p>
<p>Tufoil for Engines</p>		<p><b><u>Tufoil for Engines</u></b> Product description:</p> <p>When Tufoil engine or diesel lubricant mixes with your engine oil, two things happen.</p> <ol style="list-style-type: none"> <li>1. Your oil is changed into a highly efficient engine treatment with an extremely low surface friction.</li> <li>2. As your engine runs, this Tufoil-enhanced oil coats your engine, filling in the “nooks and crannies”.</li> </ol> <p>Guinness of World Record since 1996 - <b>“Worlds Most Effective Lubricant.”</b></p>
<p>Lightning Grease</p>		<p><b><u>Lightning Grease</u></b> Product description:</p> <p>Lightning Grease (a jelled version of Tufoil) works where all others fail. Field tests show that Lightning Grease extends the life of crucial machine parts. Lightning Grease significantly lowers operating temperatures, thereby extending machinery and bearing life. This easily-sheared grease is great for applications where low break-out torque, low temperature, stick slip and wear are required.</p>
<p>Lubit-8</p>		<p><b><u>Lubit - 8</u></b> Product description:</p> <p>Lubit-8 is a versatile, general-purpose lubricant that prevents rust and acts as a cleaning agent leaving no oily residue. It can stop locks from freezing, penetrate deeply to free “frozen” nuts and bolts, stop squeaks, and free up sticky door locks. Every home, office, and tool box should have one.</p>



CHEMFLOW PRODUCTS is an Associate Member of the Chlorine Institute.

### Contact Information

E-mail: [sales@chemflowproducts.com](mailto:sales@chemflowproducts.com)  
Web: [www.chemflowproducts.com](http://www.chemflowproducts.com)

Texas Sales/Warehouse  
13623 Poplar Circle, Suite 101  
Conroe, TX 77304  
PH: (281) 354-9594  
FX: (832) 201-7550

Louisiana Sales/Warehouse  
8480 Athens Avenue  
Baton Rouge, LA 70814  
PH: (225) 330-6592  
FX: (225) 612-6620

