CBR Series

Robust Lined Butterfly Valves

Engineered specifically for the most demanding lined butterfly valve applications





Features:

- Unmatched resistance to Permeation Related Valve Failure
- 8mm Thick Modified Teflon Lining
- ONLY Chemours™ Teflon™ NXT or Dyneon™ TFM™ resins used
- Viton Seat Backing Ring
- Duplex Disc/Stem w/ extra thick PFA Liner
- Full Vacuum Rated
- Investment Cast WCB Bodies w/ Robust **Epoxy Paint System**
- Locking Lever Handle or Gear
- ISO 5211 Mounting Pad
- Sizes 2" to 24"
- Stock Deliveries
- Serial numbered and fully traceable

Distributed by:



UNP Polyvalves - CBR Series

MOC and Ordering Information:

ASTM A216 Gr. WCB Body

Disc/Stem Duplex w/ PFA

Liner/Seat 8mm Thick Modified PTFE

Seat Pad Viton

PTFE / Viton Packing **Bolting** ASTM A193 Gr. B7

Sizes 2" to 24"

Body Styles Wafer, Semi-Lug or Full Lug Lever to 4", Gear 6" & above Operator

Order Information:

Wafer #BFWR-C1-T5-L1-TVCBR-F5-X-Y-XX #BFSL-C1-T5-L1-TVCBR-F5-X-Y-XX Semi-lua Lug Tapped #BFFL-C1-T5-L1-TVCBR-F5-X-Y-XX

X = L for size 2" - 4"; G for size 6" - 24"

Houston:

13623 Poplar Circle, Suite 101 Conroe, TX 77304 PH: (281) 354-9594 FX: (832) 201-7550

s@chemflowproducts.com

Baton Rouge Sales: Baton Rouge, LA

PH: (225) 330-6592

Or the Brand of your Choice!

QTRCO

Air Torque

El-O-Matic

Habonim Compact II



